

XS900TGT6I

90 cm, FRIDGE AND FREEZER, OT Model

BUILT-IN

X-PRO® SERIES



Fhiaba



FEATURES

- Made in Italy: Designed and built entirely in Italy with artisanal precision
- Long Term Reliability: Premium materials and rigorous testing ensure consistent, durable performance
- Galvanized Steel Structure: Strength and stability engineered to last
- Antibacterial Interior: Hygienic surfaces preserving freshness and bottle quality
- EventLift™: Shelves adjustable to any height without removal
- ProVent™: Uniform cold air distribution across every zone
- EquiLance™: Patented variable pivot hinge for silent, stable movement
- OptiView™: Diffuse, uniform LED lighting
- Full Colour TFT Display: Clear, intuitive, high definition interface
- 100% Total No Frost: Automatic system that prevents ice formation and ensures impeccable humidity control
- Variable Speed Compressors: Precise temperature control and reduced vibrations
- Sabbath Mode: Dedicated function for observance needs
- Easy Installation: Adjustable front feet and rear wheels
- Low Temperature Zone: Dedicated area with a temperature 2°C lower than the refrigerator compartment, ideal for meat, fish, and vegetables
- Tempered Glass Shelves: With aluminum profiles
- TriMode™: Lower drawer configurable as refrigerator, fresh zone, or freezer

GENERAL PROPERTIES

Equilance Hinge	YES
Soft-Closing Glides	YES
Low Vibration	YES
OptiView (Led Light Spots)	YES
Shelves	4 - 1 fixed 3 adjustable
Type Of Shelves	GLASS
Door Bins	3
Fridge Interior Drawers	2
Freezer Drawers	1
Evenlift Shelves	YES
Full Extension Shelves 90° Door Opening	NO
Full Extension Drawers 90° Door Opening	YES
Defrost Process	AUTOMATIC
Ice Maker With Water Filter	YES
Door Open Alarms	YES
Shopping Fridge	YES
Shopping Freezer	YES
Power Failure Alert	YES
Water Dispenser With Water Filter	NO


XS900TGT6I

90 cm, FRIDGE AND FREEZER, OT Model

BUILT-IN

X-PRO® SERIES

PRODUCT DETAIL



1D | 1BD | 2M

D = door

BD = drawer

M = separate microclimates

CAPACITY		DIMENSIONS & WEIGHT	
Volume Compartment 1 (L)	425	Height of the product (closed weels)(mm)	2120
Volume Compartment 2 (L)	N/A	Adjustable feet height (mm)	25
Volume Compartment 3 (L)	131	Width of the product (mm)	899
Total Net Volume (L)	556	Depth of Product without handle (mm)	635
Total Gross Volume (L)	581	Wall cavity height (mm)	2134
Compartment 1 / Upper wine cellar capacity (bottles)	N/A	Wall cavity width (mm)	900
Compartment 2 / Lower wine cellar capacity (bottles)	N/A	Wall cavity depth (mm)	650
Compartment 3 / Bottom wine cellar capacity (bottles)	N/A	Net Weight (kg)	214
		Gross Weight (kg)	235
TECHNICAL DETAILS		TEMPERATURE RANGES	
Total absorbed current (A)	2	Climatic compartments	2
Voltage (V)	220-240V	Compartment 1 / Upper temperature (°C)	from 2 to 8
Frequency (Hz)	50/60 Hz	Compartment 2 / Middle temperature (°C)	from N/A to N/A
Power Cord Length (mm)	2	Low temp zone	YES
Plug Type	Tipo F (Schuko) 16A IEC13 10A	Compartment 3 / Low temperature (°C)	from -15 to -22
Climatic class	SN/T	Dual zone	YES
Noise level (dB)	41	ACCESSORIES	
Refrigerant (gas)	R600a	• Stainless steel sides panels • Glass door • Ice maker with water filter • Water filtration system • Joining kit • X-Pro top grille kit • Extra length anti-tipping kit • Anti-condensation kit • Cleaning kit • Water filter cartridge • FLD - Fhiaba Link Device • Painting • 90° Door stop	
Water connection / female attachment	female 3/4"		
EFFICIENCY			
New Energy Label class	E		
Energy consumption (kWh/year)	273		

XS900TGT6I



90 cm, FRIDGE AND FREEZER, OT Model

BUILT-IN

X-PRO® SERIES


PRODUCT SPECIFICATIONS AND DIMENSIONS

Fhiaba




FRONT VIEW

SIDE VIEW




TECHNICAL DATA	
Niche Width A (mm)	900
Unit Width B (mm)	887
Unit Width with lateral frames C (mm)	899


TOP VIEW,
HINGE 105°



TOP VIEW,
HINGE 90°



PLINTH SIZE



i For installation specifications, please consult with Fhiaba. For optimum installation, we recommend using the actual product as the best guide.

i Based on the adjustment of the feet and the height of the panel from the floor, the customer defines the perforated plinth to be installed on the equipment.

XS900TGT6I


90 cm, FRIDGE AND FREEZER, OT Model

BUILT-IN



X-PRO® SERIES

PRODUCT SPECIFICATIONS AND DIMENSIONS

Fhiaba




Electrical Connection



Electrical and water connections (if applicable) should be reachable without having to uninstall the appliance. If the connections must be made directly behind the appliance then it is recommended to recess those connections.

IMPORTANT: do not put the water shut-off valve behind the appliance where it will be inaccessible.



For installation specifications, please consult with Fhiaba. For optimum installation, we recommend using the actual product as the best guide.

f YouTube Instagram in
www.fhiaba.com

4/4